

15LV/M15LV Series Mini Valve



Features:

- | Maximum allowable working pressure to 15,000 PSI
- | Multiple connection sizes available
- | Temperature ranging from -100°F to 600°F (-73°C to 315°C)
- | Body material - 316SS
- | Integral through holes for bracket mounting
- | Non-rotating vee stem
- | Coated 17-4PH vee stem
- | Standard with T-handle or optional knob handle

Benefits:

- | Compact size
- | DLC coating for longer stem life
- | Complete line of fittings and tubing available

BuTech Pressure Systems is pleased to introduce into our line of valves, fittings and tubing, the "Mini Valve". This valve is available with the option of either imperial connections or metric connections and metric packing gland. The metric valve is designed to be used with imperial size tubing and metric tools. Available in three different body patterns; 2-way straight, 2-way angled and 3-way/one on pressure.

Catalog Number Selection

Valve Series	Connection	Size	Flow Path	Stem Tip	Options
15LV (Imperial) M15LV (Metric)	H High Pressure M Medium Pressure P Pipe	2 - 1/8" 4 - 1/4"	1 2-way straight 2 2-way angle 4 3-way/1 on pressure	V	PH - Plastic Knob (T-handle std)

DATA SHEET

BuTech
PRESSURE SYSTEMS



Manufacturer of High Pressure Valves & Fittings Since 1973

4928 Pittsburgh Avenue • Erie, PA 16509
Phone: 814-833-4904 • Fax: 814-833-2612
www.butech-valve.com

